

Energy Division

Raychem MV Surge Arresters RDA for Indoor Applications



Raychem MV Surge Arresters RDA for Indoor Applications


In gas-insulated switchgear systems RDA type

Modern gas-insulated switchgear connected to combined underground and overhead distribution systems are sensitive to effects like transient voltage doubling. An arrester installed right at the cable end will clamp the voltage to a level which does not put the switchgear at risk.

The RDA surge arrester, together with the Raychem RICS connection system for gas-insulated switchgear, facilities at hermetically sealed integration of the arrester and the cable termination to be connected to a switchgear. Compact design and easy installation are the special features of this product line.

Generic technical data:

RDA-xx series		6-24 kV Uc		
Rated discharge	10 kA			
Line discharge c	Class 1			
Operating duty	100 kA			
Long duration c	400 A			
10 second temp	1.25			
High current sho (Safe non-shatte	16 kA			
Energy	line discharge impulse high current impulse	2.6 kJ/kV Uc 5.3 kJ/kV Uc		



RDA	Height L (mm)				
RDA-06	138+222				
RDA-09	168+222				
RDA-12	200+222				
RDA-15	299+222				
RDA-18	329+222				
RDA-21	361+222				
RDA-24	393+222				

Protective Characteristics

RDA	Uc	Ur kV	Ures in	Ures in kV when tested to impulse waveforms					
	kV		Lightning (8/20µs)			Steep lightning (1/20µs)	Switching (30/60µs)		
			5kA	10kA	20kA	40kA	10kA	125A	500A
RDA-06	6	7.5	18.6	20.0	22.4	26.2	21.8	13.8	14.8
RDA-09	9	11.0	27.9	30.0	33.6	39.3	32.7	20.6	22.2
RDA-10	10	12.5	31.0	33.3	37.4	43.7	36.3	22.9	24.7
RDA-12	12	15.0	37.2	40.0	44.9	52.4	43.6	27.5	29.6
RDA-15	15	18.0	46.5	50.0	56.1	65.5	54.5	34.4	37.0
RDA-18	18	22.0	55.8	60.0	67.3	78.6	65.4	41.3	44.4
RDA-21	21	26.0	65.1	70.0	78.5	91.7	76.3	48.1	51.8
RDA-24	24	30.0	74.4	80.0	89.7	105.0	87.2	55.0	59.2

Uc: Continous Voltage; Ur: Rated Voltage; Ures: Residual Voltage

Arresters for other voltages are available on request.

While Tyco Electronics and its affiliates referenced herein have made every reasonable effort to ensure the accuracy of the information contained in this catalog, Tyco Electronics cannot assure that this information is error free. For this reason, Tyco Electronics does not make any representation or offer any guarantee that such information is accurate, correct, reliable or current. Tyco Electronics reserves the right to make any adjustments to the information at any time. Tyco Electronics expressly disclaims any implied warranty regarding the information contained herein, including, but not limited to, the implied warranties of merchantability or fliens for a particular purpose. Tyco Electronics' only obligations are those stated in Tyco Electronics' Standard Terms and Conditions of Sale. Tyco Electronics will in no case be liable for any incidental, indirect or consequential damages arising from or in connection with, including, but not limited to, the sale, resale, use or misuse of its products. Users should rely on their own judgement to evaluate the suitability of a product for a certain purpose and test each product for its intended application. In case of any potential ambiguities or questions, please don't hesitate to contact us for clarification. Raychem, TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Energy Division - innovative and economical solutions for the electrical power industry: cable accessories, connectors & fittings, insulators & insulation, surge arresters, switching equipment, lighting controls, power measurement and control.

Tyco Electronics Raychem GmbH Energy Division Finsinger Feld 1 85521 Ottobrunn/Munich, Germany

Phone: +49-89-6089-0 Fax: +49-89-6096345

